



Automotive and Transportation
Solutions



SMART LUBRICATION™ SOLUTIONS FOR VEHICLE CHASSIS & BRAKE SYSTEMS

Smart science drives handling performance innovation



DESIGN FOR OPTIMIZED HANDLING PERFORMANCE

Meet your critical lubrication requirements for advanced chassis and brake systems design with *Molykote*[®] brand specialty lubricants from Dow Corning, a wholly owned subsidiary of The Dow Chemical Company. With our in-depth expertise, a heritage of innovation, problem-solving collaboration, and reliable global supply and technical support, these high-performance *Smart Lubrication*[™] solutions are precisely formulated and application-matched to help you achieve:

- **Energy efficiency** with reduced friction losses and increased wear control
- **Comfort and design** with enhanced smoothness and reduced noise and vibration
- **Safety** with added component reliability, less wear and more corrosion resistance
- **Sustainability** with increased process efficiency and durable component service life

Design for optimized handling performance with a choice of *Molykote* brand *Smart Lubrication* solutions:

- **Greases** with special additives to resist water washout, evaporation or oxidation
- **Silicone compounds** for light-load lubricating and sealing in extreme temperatures
- **Anti-seize pastes** with high levels of lubricating solids for heavy loads and slow speeds
- **Anti-friction coatings** for clean dry-film lubrication to control friction, wear and noise
- **Solids and powders** for plastics lubrication and specialized friction-control additives
- **Oils and dispersions** with performance additives in synthetic or mineral blends

INNOVATE WITH SMART SCIENCE

Proven, effective *Molykote* brand *Smart Lubrication* solutions can help you meet chassis and brake system design goals for handling performance innovation:

Improve braking performance; reduce noise and vibration

- Pedal systems, parking brakes
- Boosters, actuators
- Caliper pins and springs
- Pad clips, shims, springs
- Drum brake components
- Pad and lining friction additives

Maintain steering response, precision and smoothness

- Steering column bearings
- Tilt-wheel adjusters
- Electric power steering
- Gears, linkage, tie rods

Reduce suspension wear and NVH

- Ball joints, axial joints, bushings
- Strut bearings

Provide lifetime lubrication for difficult-to-access components

- Parking brake cables, gears
- Assembly fasteners



MOLYKOTE[®]
FROM DOW CORNING



SMART LUBRICATION™ SELECTION GUIDE: CHASSIS & BRAKE APPLICATIONS

APPLICATION	DESIGN NEED	POTENTIAL SOLUTION(S)	PRODUCT HIGHLIGHTS
Booster/Actuator	Reduced friction and wear	<i>Molykote</i> ® PG-54 Grease	Silicone-oil-based grease with excellent elastomer compatibility
		<i>Molykote</i> ® 111 Compound	Silicone-oil-based compound with wide service-temperature range
Brake Clips, Springs	Controlled friction and wear in extreme temperatures	<i>Molykote</i> ® D-708 Anti-Friction Coating	Heat-cured, PTFE-based AFC for controlled friction with minimal wear
		<i>Molykote</i> ® D-7405 Anti-Friction Coating	Heat-cured AFC with low coefficient of friction and good corrosion protection
Brake Pad Shims	Reduced friction and wear	<i>Molykote</i> ® M-77 Solid Lubricant Paste	Silicone oil with thickener system and MoS ₂ solids
Caliper Pins	Reduced fretting corrosion, NVH and abnormal pad/rotor wear	<i>Molykote</i> ® G-3407 Caliper Pin Grease	Synthetic PAG-based grease for reducing fretting resistance in metal-metal pairings
		<i>Molykote</i> ® G-807 Low Friction Silicone Compound	PTFE-modified compound for rubber-to-metal and plastic-to-metal lubrication
Drum Brake Components	Reduced friction, wear and brake drag	<i>Molykote</i> ® 44M Grease	Silicone-oil-based grease with good water resistance
		<i>Molykote</i> ® G-n Metal Assembly Paste	Synthetic MoS ₂ -based lubricant with very low sliding friction for component run-in
Electric Parking Brake	Lifetime lubrication with improved performance	<i>Molykote</i> ® E Paste	Synthetic paste with several types of special solid lubricants
		<i>Molykote</i> ® AG-633 Grease	Synthetic grease for plastic parts lubrication
		<i>Molykote</i> ® D-708 Anti-Friction Coating	Heat-cured, PTFE-based AFC with excellent corrosion protection
Brake Pads, Linings	Reduced wear, fading and vibration	<i>Molykote</i> ® Lubolid Additive Powders	Inorganic-based additives for more precise friction control in pads and linings
Pedal Systems	Reduced friction with improved smoothness	<i>Molykote</i> ® 106 Anti-Friction Coating	Heat-cured, dry-film AFC for clean, lifetime lubrication unaffected by dust and dirt
		<i>Molykote</i> ® D-7409 Anti-Friction Coating	Heat-cured, MoS ₂ -based AFC with outstanding lubrication
Steering System	Reduced friction, wear and noise	<i>Molykote</i> ® EM-30L Grease	Synthetic grease for lubricating plastic components
		<i>Molykote</i> ® D-7409 Anti-Friction Coating	Heat-cured, MoS ₂ -based AFC with outstanding lubrication
Suspension, Axle Ball Joints	Reduced friction and wear in severe-duty service	<i>Molykote</i> ® G-4700 Extreme Pressure Synthetic Grease	NLGI GC-LB-certified extreme-pressure grease for heavy loads and vibrations
		<i>Molykote</i> ® Longterm 2/78G High Performance Grease	Mineral-oil-based grease with high load-bearing capability
Suspension Strut Bearings	Reduced friction and wear	<i>Molykote</i> ® Longterm 2 Plus Bearing Grease	Mineral-oil-based grease with solid lubricants and extreme-pressure additives
Assembly Fasteners, Bolts	Improved assembly with proper tightening torque	<i>Molykote</i> ® D-7405 Anti-Friction Coating	Heat-cured AFC with low coefficient of friction and good corrosion protection
		<i>Molykote</i> ® D-321 R Anti-Friction Coating	Air-drying bonded lubricant with excellent heat-aging resistance under heavy loads

NOTE: These are proven, effective *Molykote*® brand *Smart Lubrication*™ solutions for vehicle chassis and brake systems design. Contact your Dow Corning representative for product options to meet specialized requirements.



SUSTAINABLE DESIGN SOLUTIONS

Enhance your design sustainability with *Molykote* brand *Smart Lubrication* solutions from Dow Corning. To meet key chassis and brake design needs, these advanced specialty lubrication technologies can be custom-formulated for specified performance characteristics, regulatory standards and process requirements. Raw materials include base oils such as silicone, mineral or polyalphaolefin (PAO); solid lubricants such as molybdenum disulfide (MoS₂) and polytetrafluoroethylene (PTFE); thickeners such as lithium; and various performance additives to inhibit rust, resist wear or withstand extreme pressure.

- *Molykote*® brand greases and anti-seize pastes reduce wear and NVH while resisting corrosion and water wash-out in safety-critical lubrication of steering, suspension and braking components.
- *Molykote*® brand anti-friction coatings optimize friction and wear control, reduce brake system noise, and remain effective in the presence of dust and dirt.
- *Molykote*® brand Lubolid additives help achieve precise friction properties for antimony-free and lead-free brake pads and linings to meet End of Life Vehicles Directive (ELV) requirements.

SMART LUBRICATION SOLUTIONS FOR OTHER VEHICLE SYSTEMS

In addition to the *Molykote* brand *Smart Lubrication* solutions for chassis and brake design featured in this selection guide, Dow Corning also offers proven, effective lubricants for these vehicle systems:

- Electrical
- Interior
- Exterior
- Powertrain

LEARN MORE: CONTACT US

To learn more about *Molykote* brand specialty lubricants and proven, effective *Smart Lubrication* solutions to drive handling performance innovation in vehicle chassis and brake systems design, contact your Dow Corning Technical Representative, visit dowcorning.com/auto or send an email via [dowcorning.com/ContactUs](mailto:contact@dowcorning.com).

Images: Cover - AV25988, AV25990, AV25989; Page 2 - AV25780, AV23571; Page 3 - AV23743, AV25397; Page 4 - AV14706

HANDLING PRECAUTIONS

PRODUCT SAFETY INFORMATION REQUIRED FOR SAFE USE IS NOT INCLUDED IN THIS DOCUMENT. BEFORE HANDLING, READ PRODUCT AND SAFETY DATA SHEETS AND CONTAINER LABELS FOR SAFE USE, PHYSICAL AND HEALTH HAZARD INFORMATION. THE SAFETY DATA SHEET IS AVAILABLE ON THE DOW CORNING WEBSITE AT DOWCORNING.COM, OR FROM YOUR DOW CORNING SALES APPLICATION ENGINEER, OR DISTRIBUTOR, OR BY CALLING DOW CORNING CUSTOMER SERVICE.

LIMITED WARRANTY INFORMATION – PLEASE READ CAREFULLY

The information contained herein is offered in good faith and is believed to be accurate. However, because conditions and methods of use of our products are beyond our control, this information should not be used in substitution for customer's tests to ensure that our products are safe, effective and fully satisfactory for the intended end use. Suggestions of use shall not be taken as inducements to infringe any patent.

Dow Corning's sole warranty is that our products will meet the sales specifications in effect at the time of shipment.

Your exclusive remedy for breach of such warranty is limited to refund of purchase price or replacement of any product shown to be other than as warranted.

TO THE FULLEST EXTENT PERMITTED BY APPLICABLE LAW, DOW CORNING SPECIFICALLY DISCLAIMS ANY OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY.

DOW CORNING DISCLAIMS LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

Dow is a registered trademark of The Dow Chemical Company.
Dow Corning is a registered trademark of Dow Corning Corporation. The Corning portion of the Dow Corning trademark is a trademark of Corning Incorporated, used under license.
Molykote is a registered trademark of Dow Corning Corporation.
Smart Lubrication and *Smart Science Drives Mobility Innovation* are trademarks of Dow Corning Corporation.

©2016 Dow Corning Corporation, a wholly owned subsidiary of The Dow Chemical Company. All rights reserved.

AGP14826

Form No. 80-8157A-01

